

UPDATE LUBE CHART

TECHNICAL INFORMATION 2014-06-16



MERCEDES-BENZ

Engine

Gasoline engines, passenger cars 229.5

Diesel engines, passenger cars 229.51

Diesel engines, passenger cars 229.52

Diesel engines, transport cars 229.51

Diesel engines, transport cars 228.51

Diesel engines, trucks 228.5

Diesel engines, trucks 228.3

Manual Transmission

Automatic Transmission

4 and 5-shift

6 shift and higher

CVT

DCT

Transfer Case

Differentials

Power Steering

Brake & Clutch System

Coolant

Midland lubricant/ fluid

Synqron 0W-40

Synova 5W-30/40/ Crypto³ 5W-30 (VW)/
Axsept 5W-30 (GM)/ Renion 5W-30 (Nissan)

Synova 5W-40

Synova 5W-30/40/ Crypto³ 5W-30 (VW)/
Axsept 5W-30 (GM)/ Renion 5W-30 (Nissan)

Maxtra 10W-40 (prolonged intervals)

Synqron Diesel 5W-30/ Maxtra 10W-40

Super Diesel 15W-40

Synqrogear 75W-80 (passenger cars)

ATF Omnimatic (236.9, 236.11)

ATF Sensomatic (236.12, 236.14, 236.15, 236.41)

JCV CVT Oil (236.20)

Dualtrans DCT Oil (236.21)

A-/ B-Class gear boxes: F-DCT350, F-DCT500

Integrated with AT using the same ATF

High Performance 75W-140 LS & EP

Power Steering Fluid (345.0)

Brake Fluid Hypro LV DOT4

XT-Coolant Long Life (325.3 for transport cars.
exceeds 325.0 for passenger cars)

- For more information see product sheets available at www.midland.ch
- For volumes, see DMS service or model search engine at www.alticar.dk