



## Econova 5W-30 | Fully synthetic engine oil

### Property

- best resistance to oxidation (ageing stability)
- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- keeps the engine clean and protects against wear and corrosion
- excellent cold starting characteristics
- very good high temperature properties
- Low SAPS technology with reduced content of sulphated ash, phosphorus and sulphur
- increases the service life of exhaust aftertreatment systems such as catalytic converters (SCR) and particulate filters (GPF/DPF) in gasoline and diesel engines

### Application area

- suitable for gasoline and diesel engines
- suitable for passenger cars and light commercial vehicles

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	5W-30
Color	-	brown
Viscosity @ 40°C	cSt	58.4
Viscosity @ 100°C	cSt	10.4
Viscosity index	-	169
Density @ 15°C	kg/l	0.852
Viscosity @ -30°C	mPa.s	4100
Viscosity HTHS @ 150°C	mPa.s	3.07
Zinc content	ppm	880
Pour Point	°C	-36
Flash Point	°C	220

### Available packaging

1 L bottle	4 L canister
Case 12 x 1 L bottles	Case 6 x 4 L canisters
175 kg drum (approx. 205 L)	

### Specifications

ACEA A1/B1*, A5/B5, C2
API SJ*, SL*, SL/CF*, SM*, SN/CF
Chrysler MS 6395
Fiat 9.55535-CR1, S1
IVECO 18-1811 S1, SC1
Jaguar Land Rover STJLR.03.5005
PSA B71 2290
Renault RN0700

\* Additional Specifications