



Econova 0W-30 | Fully synthetic engine oil

Property

- best resistance to oxidation (ageing stability)
- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- keeps the engine clean and protects against wear and corrosion
- excellent cold starting characteristics
- good high temperature properties
- Low SAPS technology with reduced content of sulphated ash, phosphorus and sulphur
- increases the service life of exhaust aftertreatment systems such as catalytic converters (SCR) and particulate filters (GPF/DPF) in gasoline and diesel engines

Application area

- especially suitable for Ford
- suitable for gasoline and diesel engines
- suitable for passenger cars and light commercial vehicles

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	0W-30
Color	-	brown
Viscosity @ 40°C	cSt	46
Viscosity @ 100°C	cSt	9.8
Viscosity index	-	206
Density @ 15°C	kg/l	0.844
Viscosity CCS @ -35°C	mPa·s	5600
Viscosity HTHS @ 150°C	mPa·s	3
NOACK [%]	-	11.3
Zinc content	ppm	880
Sulphated ash	g/100g	0.8
Pour Point	°C	-42
Flash Point	°C	221

Available packaging

1 L bottle	Case 12 x 1 L bottles
175 kg drum (approx. 207 L)	

Specifications

ACEA C2
Chrysler MS 6395
Fiat 9.55535-DS1, GS1
Ford M2C950-A
IVECO 18-1811 SC1 LV
Jaguar Land Rover STJLR.03.5007