



## Super Diesel 15W-40 | Mineral Engine oil

### Property

- best resistance to oxidation (ageing stability)
- keeps the engine clean and protects against wear and corrosion
- very good high temperature properties

### Application area

- suitable for freshwater and saltwater boat engines
- backward compatibility from Euro 5 to Euro 1
- especially suitable for Volvo Penta marine engines
- suitable for cars
- suitable for gasoline and diesel engines
- suitable for light and heavy-duty commercial vehicles

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	15W-40
Color	-	brown
Viscosity @ 40°C	cSt	104.8
Viscosity @ 100°C	cSt	14.3
Viscosity index	-	139
Density @ 15°C	kg/l	0.874
Viscosity CCS @ -20°C	mPa·s	6230
Zinc content	ppm	1400
Sulphated ash	g/100g	1.1
Total base number	mg KOH/g	10
Pour Point	°C	-30
Flash Point	°C	215

### Available packaging

1 L bottle	4 L canister
Case 12 x 1 L bottles	Case 6 x 4 L canisters
25 L pail	54 kg drum (approx. 62 L)
180 kg drum (approx. 206 L)	

### Specifications

ACEA A2/B2*, A3/B3*, A3/B4, E2*, E3*, E5, E7
API CF*, CF-4*, CG-4*, CH-4*, CI-4, SL
Caterpillar ECF-1*, ECF-1a
Cummins CES 20071*, 20072*, 20075*, 20076, 20077, 20078
Global DHD-1
IVECO 18-1804 T2 E7
Mack EO-N Premium Plus
MAN M 3275-1
MB 228.1*, 228.3
MTU Type 2
PSA B71 2295
Renault RVI RLD*, RLD-2
Volvo VDS-3

\* Additional Specifications