



Unitrac STOU 10W-40 | Multi-purpose tractor oil (STOU)

Property

- best resistance to oxidation (ageing stability)
- good cold starting characteristics
- very good high temperature properties
- excellent detergent and dispersant properties (cleans and dirt cannot form deposits)

Application area

- universally suitable for engines, transmissions, hydraulic systems, wet brakes and final drives

Note

- May also be used as hydraulic fluid if a HLP 46, HLP 68, HVLP 68 or HVLP-D is specified.
- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	10W-40 / 80W-90
Color	-	brown
Viscosity @ 40°C	cSt	91.36
Viscosity @ 100°C	cSt	14.44
Viscosity index	-	164
Density @ 15°C	kg/l	0.861
Pour Point	°C	-33
Flash Point	°C	221

Available packaging

54 kg drum (approx. 63 L)	180 kg drum (approx. 209 L)
---------------------------	-----------------------------

Specifications

ACEA E2
Allison C-3*, C-4
API CF*, CF-4*, CG-4, GL-4
Caterpillar TO-2
Ford M2C159-C
John Deere JDM J27
Massey Ferguson CMS M1135, M1139, M1144, M1145
ZF TE-ML 06B, 06C, 06D, 06F, 06Q, 06R, 07B

* Additional Specifications