



## AW 68 | Hydraulic and compressor fluid

### Property

- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- good water and air separation capacity
- excellent filterability
- free of zinc and ash

### Application area

- for compressors with compression temperatures up to 220°C
- suitable for hydraulic systems and compressors

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity ISO	-	68
Color	-	light yellow
Viscosity @ 40°C	cSt	68
Viscosity @ 100°C	cSt	9.03
Viscosity index	-	107
Density @ 15°C	kg/l	0.86
Pour Point	°C	-30
Flash Point	°C	220

### Available packaging

25 L pail	50 kg drum (approx. 58 L)
175 kg drum (approx. 203 L)	

### Specifications

AFNOR NF E 48-603 HM
Cincinnati Milacron P-69
DIN 51506 VBL, VCL, VDL
DIN 51524-2 HLP
Eaton Vickers I-286-S, M-2950-S
ISO 6743-4 HM
ISO 11158 HM
ISO/DP 6521 DAA, DAB, DAG, DAH
Parker Denison HF-0, HF-1, HF-2
US Steel 136, 137